

PRODUCT DATA SHEET

EVERBUILD STICK2[®] Touch Up Enamel

Premium quality high gloss enamel

PRODUCT DESCRIPTION

EVERBUILD STICK2[®] Touch Up Enamel is a premium quality, high gloss enamel that provides superior rust protection and dries to a mirror like finish. It is ideal for touching up scratches and chips or enamel and lacquer damages on bathroom fixtures, kitchen appliances and ceramics. It is highly durable and provides excellent colour retention, even after repeated cleaning.

USES

For use on metal and painted surfaces for touching up chips and lacquer damage.

CHARACTERISTICS / ADVANTAGES

- Resistant to weathering.
- Excellent colour retention (even after repeated cleaning).
- Quick drying.

PRODUCT INFORMATION

Packaging	25 ml
Appearance / Colour	White liquid
Shelf Life	12 months from date of manufacture in original unopened containers.
Storage Conditions	Store in cool dry conditions between 0 and +20 °C. Storage outside these parameters will dramatically reduce shelf life.
Density	ca.1 g/cm ³ at 20 °C

VALUE BASE

All technical data stated in this Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

LIMITATIONS

As the manufacturer cannot know all the uses its products may be put to, it is the users responsibility to determine suitability of use. If in doubt, contact Technical Services Department for advice.

ECOLOGY, HEALTH AND SAFETY

User must read the most recent corresponding Safety

Data Sheets (SDS) before using any products. The SDS provides information and advice on the safe handling, storage and disposal of chemical products and contains physical, ecological, toxicological and other safety-related data.

APPLICATION INSTRUCTIONS**SUBSTRATE QUALITY / PRE-TREATMENT**

Ensure surfaces are dry, clean and free from rust and grease.

APPLICATION METHOD / TOOLS

We always recommend gloves be worn when handling this product.

Apply a thin layer of EVERBUILD STICK2® Touch Up Enamel directly onto the surface using the brush included. Allow first layer to dry before repeating procedure if necessary. Allow to dry for 24 hours.

LOCAL RESTRICTIONS

Note that as a result of specific local regulations the declared data and recommended uses for this product may vary from country to country. Consult the local Product Data Sheet for exact product data and uses.

LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

SIKA LIMITED

Watchmead
Welwyn Garden City
Hertfordshire, AL7 1BQ
Tel: 01707 394444
Web: www.sika.co.uk
Twitter: @SikaLimited